2024

# Mine Hill Township

10 Baker Street, Mine Hill, New Jersey 07803 862-437-1197 **Zoning@MineHill.com** Fax: 973-366-1626



### CH APPLICATION for SALE of RESIDENTIAL PROPERTY

					$\mathbf{C}$	H # 24		
Block	Lot	Sti	reet Address					
1. Owner's N	lame	· · · · · · · · · · · · · · · · · · ·		PI	hone #:		· · · · · · · · · · · · · · · · · · ·	
Address (if oth	ner than above)			E	mail:			
2. Buyer's Name Intends to Occupy Re							Out	
			Phone #					
3. Owner's A	Attorney		Phone #					
4. Buyer's A	ttorney			Phone #				
5. Number o	of dwelling units		Numb	Number of Floors (including basement)				
6. <b>Pools:</b> Al	bove Ground	In-Ground _	Hot tub _	Type of Heat:	Gas	_ Oil	Electric	
7. Number o	of: Bedrooms	_ Kitchens	Bathrooms	_ Sheds/Garages	Is there a	: Basement _	Attic	
If the prope inspector is	rty has a septi- required. Prod ls, please contac	c system, a co of of a well de ct the Health D	opy of a seption commissioning Department at	c inspection report of g is also required. I 973-691-0900 x7330	by an eng If you have ). Check a	ineer or a e any quest ll that appl	certified septic	
Single Family_				Condo Other _				
Email:				o whomever you wis				
To Set Up		nent to Cond	duct the Ins	pections, the Tow	nship's lı	nspector s	shall Contact	
Name:_	tification I here	by certify that a	ıll the information		`my knowle	edge, and bel		

Date:\_\_\_\_\_

Owner's Signature:

## Selling of Residential Properties in Mine Hill Township

Certificate of Habitability. The Certificate of Habitability Ordinance requires that the owner of any property that is being sold obtain a Certificate, which MUST be obtained before the new occupancy takes place. Also included, but not limited to:

House number must be clearly visible, at least 2 1/4 inches high and in contrast with the background color. If the house is located off the street, the number must be placed on the mailbox or other suitable location that can be seen by the Fire Department.

#### **Items to be addressed:**

- All open construction permits and violations must be closed out.
- 10-Year sealed battery smoke and carbon monoxide detectors are properly installed as outlined below.
- All carbon monoxide detectors, smoke detectors, and fire extinguishers should be located as per NJ Administrative Code 5:70-4.19.
- Health Department Certificate of Completion. Please contact the Health Department at 973-691-0900 x 7330 regarding:
  - If the property is connected to town water, the well must be decommissioned by a professional well driller prior to the transfer of sale and a Well Decommissioning Report provided.
  - If the property has a septic system, a copy of the septic inspection report by an engineer or a certified septic inspector is required.

#### Pools/Hot tubs

- All pools must have a fence or wall at least 48 inches high around the pool area. Above ground pools at least 48 inches above ground level generally satisfy this requirement. Fences must meet the minimum state requirements.
- All gates having access to the pool area must be at least 48 inches in height, opening out, self-closing, self-latching. The release must be at least 54 inches above ground level. This applies to above ground pools, too.
- If there are no permits for the pool and/or a hot tub, the CCO will not be issued until the permits are procured and satisfactory inspections are done by the Building Department.

Certificate of Habitability does not replace or supersede a home inspection.

### Smoke and Carbon Monoxide Detectors & Fire Extinguisher Certification Requirements

electrically powered, interconnected smoke alarms must maintain that corner. system in working order and may **not** be converted to batteryoperated alarms.

All smoke alarms must be less that 10 years old and UL listed. Any new smoke alarm **must** be a sealed 10-year life unit.

Any home constructed prior to the code requirements for 110-volt Plug-in electrically powered carbon monoxide alarms may be plugged smoke alarm on every level of the home, including the basement and the bedroom and within ten (10) feet of the bedroom doors. habitable attic. Additional alarms would be required in attics and crawl spaces under the home if they contain the boiler/furnace, water heater or other combustion-producing appliances.

All smoke alarms must be permanently mounted to the ceiling. If ceiling mounting is not possible, the alarm should be permanently mounted on the wall, at least four (4) inches down from the ceiling, with the bottom of the alarm within twelve (12) inches of the ceiling. Smoke alarms must be at least four (4) inches away from the wall/ **ceiling corner** (see Diagram A).

Smoke alarms are required to be located in the hallway/outside bedrooms within ten (10) feet from all bedroom doors (Diagram B).

Basement smoke alarms should be located in close proximity to the 2. bottom of the basement stairs.


When required, crawl space and attic smoke alarms should be located within arm's reach of the entrance to the space.

Carbon Monoxide Alarms must be located on all levels that have 5. bedrooms. They are required to be located in the hallway/outside

bedrooms within ten (10)feet of all bedroom doors.

Carbon monoxide alarms may electrically hardwired as part of the smoke alarm system, electrically powered type, plug-in battery.

Combination smoke/ carbon monoxide alarms must be permanently mounted



Smoke Detector Requirements. Any home constructed with 110-volt to the ceiling at least four (4) inches away from the ceiling/wall

Battery operated carbon monoxide alarms must be permanently mounted in accordance with the manufacturer's instructions (normally wall mounted, approximately four (4) to six (6) feet above floor

powered smoke alarms must have at least one (1) battery-operated directly into an electrical outlet that is located in the hallway/outside

Effective September 1, 2018, the following requirements regarding Fire Extinguishers for resale will be enforced under the new NJ Uniform **Fire Code Requirements:** 

- The extinguisher shall be within 10 feet of the kitchen and located in the path of egress directly to the exterior of the home. Doors that lead to a deck without stairs or to a garage are not considered exits.
- If the kitchen has a door, it must be mounted in the kitchen.
- It must be readily accessible and not obstructed from view.
- It must be mounted using the manufacturer's hanging bracket so the operating instructions are clearly visible.
- It must have a minimum rating of 2A-10:BC and no more than 10 pounds.
- It shall be serviced and tagged by a certified Division of Fire Safety contractor within the past 12 months or the seller must have a receipt for recently purchased extinguisher.
- The owner's manual or written operation instructions shall be provided during the inspection and left for the new occupant.
- The top of the extinguisher shall not be more than five feet above the floor.

No Certificate of Habitability will be issued unless all of the above requirements have been met.

> Online at: Www.MineHill.com

