**2025** 

## **Mine Hill Township**

10 Baker Street, Mine Hill, New Jersey 07803 862-437-1197 **Zoning@MineHill.com** Fax: 973-366-1626



## CH APPLICATION for SALE of RESIDENTIAL PROPERTY

					CH # 25	<del> </del>
Block	Lot	Street Address	· · · · · · · · · · · · · · · · · · ·			
	ame					
Address (if othe	er than above)		E	mail:		
2. Buyer's Na	ame		Intends to C	Ссиру	Rent	t Out
Current Addres	ss		P	hone #_		· · · · · · · · · · · · · · · · · · ·
3. Owner's A	ttorney		F	hone #_		
4. Buyer's At	torney		F	hone #_		
5. Number of	f dwelling units	Number	of Floors (including	baseme	nt)	
6. <b>Pools:</b> Ab	ove Ground In-Grou	nd Hot tub	Type of Heat:	Gas	Oil	_ Electric
7. Number of	f: Bedrooms Kitchens	Bathrooms S	Sheds/Garages	Is there	a: Basement	t Attic
8. If a copy of	f your survey is available, pl	ease attach it to the ap	plication.			
	er Smoke/Carbon Monoxiong in the proper location.	de Detectors must be	e in proper working	g order.	Fire Extingu	isher must be
10. Closing D	Pate:					
11. FEE:	\$	175 must accompa	any the application			
inspector is	rty has a septic system, required. Proof of a we ls, please contact the Hea	ll decommissioning	is also required.	If you h	ave any que	estions regarding
	Septic Cesspool	Town Sewer	Private Well	_ Town '	Water	
Single Family_	Duplex Multi-Fam	nily Townhouse/Co	ondo Other _	(Des	cribe)	
ı						
	Your approved CH is e-	_	_			_
Email:		Email:				
To Set Up	an Appointment to C	Conduct the Inspe	ctions, the Tow	nship's	Inspector	shall Contact
Name:			_ Phone:			· · · · · · · · · · · · · · · · · · ·
	<b>tification</b> I hereby certify the egoing information is willing					belief. I am aware
O , G.	·	<del>-</del> - ·	Dota		-	

# See other side for new requirements.

## Selling of Residential Properties in Mine Hill Township

Certificate of Habitability. The Certificate of Habitability Ordinance requires that the owner of any property that is being sold obtain a Certificate, which MUST be obtained before the new occupancy takes place. Also included, but not limited to:

House number must be clearly visible, at least 2 1/4 inches high and in contrast with the background color. If the house is located off the street, the number must be placed on the mailbox or other suitable location that can be seen by the Fire Department.

#### **Items to be addressed:**

- All open construction permits and violations must be closed out.
- 10-Year sealed battery smoke and carbon monoxide detectors are properly installed as outlined below.
- All carbon monoxide detectors, smoke detectors, and fire extinguishers should be located as per NJ Administrative Code 5:70-4.19.
- Health Department Certificate of Completion. Please contact the Health Department at 973-691-0900 x 7330 regarding:
  - If the property is connected to town water, the well must be decommissioned by a professional well driller prior to the transfer of sale and a Well Decommissioning Report provided.
  - If the property has a septic system, a copy of the septic inspection report by an engineer or a certified septic inspector is required.

#### Pools/Hot tubs

- All pools must have a fence or wall at least 48 inches high around the pool area. Above ground pools at least 48 inches above ground level generally satisfy this requirement. Fences must meet the minimum state requirements.
- All gates having access to the pool area must be at least 48 inches in height, opening out, self-closing, self-latching. The release must be at least 54 inches above ground level. This applies to above ground pools, too.
- If there are no permits for the pool and/or a hot tub, the CCO will not be issued until the permits are procured and satisfactory inspections are done by the Building Department.

Certificate of Habitability does not replace or supersede a home inspection.

### Smoke and Carbon Monoxide Detectors & Fire Extinguisher Certification Requirements

Smoke Detector Requirements. Any home constructed with 110-volt four (4) inches away from the ceiling/wall corner. electrically powered, interconnected smoke alarms must maintain that system in working order and may not be converted to batteryoperated alarms.

All smoke alarms must be less that 10 years old and UL listed. Any new smoke alarm **must** be a sealed 10-year life unit.

Any home constructed prior to the code requirements for 110-volt directly into an electrical outlet that is located in the hallway/outside powered smoke alarms must have at least one (1) battery-operated the bedroom and within ten (10) feet of the bedroom doors. smoke alarm on every level of the home, including the basement and habitable attic. Additional alarms would be required in attics and crawl spaces under the home if they contain the boiler/furnace, water heater or other combustion-producing appliances.

All smoke alarms must be permanently mounted to the ceiling. If ceiling mounting is not possible, the alarm should be permanently mounted on the wall, at least four (4) inches down from the ceiling, with the bottom of the alarm within twelve (12) inches of the ceiling. Smoke alarms must be at least four (4) inches away from the wall/ **ceiling corner** (see Diagram A).

Smoke alarms are required to be located in the hallway/outside • bedrooms within ten (10) feet from all bedroom doors (Diagram B).

Basement smoke alarms should be located in close proximity to the bottom of the basement stairs.


When required, crawl space and attic smoke alarms should be located within arm's reach of the entrance to the space.

Carbon Monoxide Alarms must be located on all levels that have bedrooms. They are required to be located in the hallway/outside

bedrooms within ten feet of (10)all bedroom doors.

Carbon monoxide alarms may electrically hardwired as part of the smoke alarm system, electrically powered plug-in type, battery.

Combination smoke/ carbon monoxide alarms must permanently mounted to the ceiling at least



Battery operated carbon monoxide alarms must be permanently mounted in accordance with the manufacturer's instructions (normally wall mounted, approximately four (4) to six (6) feet above floor

Plug-in electrically powered carbon monoxide alarms may be plugged

FIRE EXTINGUISHERS ARE <u>NO LONGER REQUIRED</u>.

### NEW STATE REQUIREMENT

## Secondary Power Source Identification Label

- A residential structure must have a label installed within 18 inches of both the main electrical panel and the electric meter warning of the dangers associated with secondary power sources.
- A secondary power source may include permanently installed internal combustion generators, solar panels, battery storage systems, or any other supplemental source of electrical energy to primary power supply.
- The label must be marked with the wording similar to "CAUTION: MULTIPLE SOURES OF POWER" and may not be handwritten. A label compliant with ANSI Z535.4 will meet the requirement of this law.



No Certificate of Habitability will be issued unless all of the above requirements have been met.